

Let us  
entertain  
you



The IW 408 is equipped with a rotating, pivoting tweeter and **WaveGuide**. As with most in-wall speakers in the 400 and 600 Custom series, they are designed with special attention to freedom of placement. Due to Jamo's clever **SoundAngle** technology, the speaker can be mounted at a height of several meters, without compromising the sound quality.

Simply set the switch to -30 degrees and the sound will be optimised downwards, aiming at the listening position. If the speaker is installed at normal height, the switch is simply set to 0 degrees.

#### Specifications

System	2-way in-wall
Woofer (mm / in)	203 / 8
Midrange (mm / in)	-
Tweeter (mm / in)	25 / 1 DTT
Power (W long / short term)	80 / 160
Frequency Range (Hz)	55 - 22,000
Impedance (Ohm)	4 - 8 switchable
Hole dimension HxWxD (mm / in)	344 x 240 x 95 / 13.5 x 9.4 x 3.7
Dimensions HxWxD (mm / in)	375 x 270 x 105 / 14.8 x 10.6 x 4.11
Back box size (Litre/in <sup>3</sup> )	22 / 1340
Weight (kg / lb)	2.2 / 4.9
Finish	White (paintable)

#### IW 408

2-way in-wall

203 / 8

-

25 / 1 DTT

80 / 160

55 - 22,000

4 - 8 switchable

344 x 240 x 95 / 13.5 x 9.4 x 3.7

375 x 270 x 105 / 14.8 x 10.6 x 4.11

22 / 1340

2.2 / 4.9

White (paintable)



*Soundwise, IW 408 is comparable with C 403, C 401, C 400 SUR*